

The Kennesaw II refractory log set features richly detailed, hand painted concrete logs for use with our HearthRite Vent-Free burner. Available in three sizes, the competitively priced Kennesaw II log set and HearthRite Burner requires minimal firebox depth making it ideal for existing fireplaces and fireboxes.

Burners are available in manual control or thermostat remote control. Both burners feature state-of-the-art Oxygen Depletion Sensor technology to ensure safe, reliable performance.



Kennesaw II Log Sets and HearthRite Vent-Free Burners

Model	Description	BTUs Input	Ship Wt.	Fits Empire Fireboxes	Minimum Firebox Dimensions in Inches			
					Front Width	Rear Width	Depth	Height
HLS18R2	Refractory Logs, 6-piece	–	22 lb.	VFD32FB/VFP32FB/VFS32FB	28	20	14	24
HLS24R2	Refractory Logs, 6-piece	–	27 lb.	VFD36FB/VFP36FB/VFS36FB	33	22	14	24
HLS30R2	Refractory Logs, 6-piece, fits 24-inch burner	–	27 lb.	VFD24FB/VFP24FB/VFS24FB	33	22	14	24
HVF2M18	Burner, 18-inch Manual	30,000 Nat/ 30,000 LP	15 lb.	VFD32FB/VFP32FB/VFS32FB	28	20	14	24
HVF2M24	Burner, 24-inch Manual	32,000 Nat/ 32,000 LP	18 lb.	VFD36FB/VFP36FB/VFS36FB	32	22	14	24
HVF2R18	Burner, 18-inch Thermostat	30,000 Nat/ 30,000 LP	17 lb.	VFD32FB/VFP32FB/VFS32FB	28	20	14	24
HVF2R24	Burner, 24-inch Thermostat	32,000 Nat/ 32,000 LP	18 lb.	VFD36FB/VFP36FB/VFS36FB	32	22	14	24

Warranty for All Models

All parts carry a one-year one-time replacement warranty.

Note: Empire Comfort Systems is committed to continuous product improvement; specifications are subject to change without notice. Flame size, shape, and color will vary from photos.

Member of the following industry associations:



This appliance is design-certified to the ANSI standard by:



SINCE 1932

918 Freeburg Ave.
Belleville, IL 62220-2623

E-mail: info@empirecomfort.com

WMH-01061 4/01/20

Empire Comfort Systems names and logos are registered U.S. trademarks.